

What is claimed is:

Sub A1
1 1. A method of conserving power consumption in a communication system which includes
2 components capable of selectively entering a low power mode and an auto-negotiation feature by
3 exchanging messages indicative of a low power mode capability, using an auto-negotiation
4 feature to interpret exchanged signals to verify that connected systems include the low power
5 mode capability, and transmitting a signal that a communications session is completed to cause
6 connected systems to enter the low power mode.

1 2. The method of claim 1 wherein said auto-negotiation feature is a next-page facility.

1 3. The method of claim 1 including a further step of employing the auto-negotiation feature
2 further to verify that the connected systems are eligible to enter the low power mode.

1 4. In a system utilizing a data communication device having a plurality of data exchange modes,
2 each of said modes operating at different speeds, one of which speeds consumes less power than
3 another, protocol means for compatibly coupling said data communication device to another
4 data communication device for exchanging data therebetween, and selection means in said data
5 communication device for a data exchange mode having a higher speed than the others, a method
6 for switching to a least power consuming speed which consumes when in an idle mode by
7 exchanging data representative of said data communication devices ability to operate at the least
8 power consuming speed, decoding via said protocol means said representative data, and changing
9 to said least power consuming speed in response to another protocol signal.

Sub A1

1 5. In a local area network which includes Ethernet data terminal equipment capable of low power
2 modes and employing auto-negotiation, a method for conserving power consumption during
3 periods of low usage by using a next-page aspect of the auto-negotiation feature to communicate
4 among terminal data equipment each equipment's capability to assume a low power mode,
5 detecting periods of low network usage, verifying in response to detection of low network usage
6 that each equipment is eligible to assume the low power mode by use of the auto-negotiation
7 feature, and asserting signals to put each eligible equipment in a low power mode of operation.

Add A17